

Single-phase On-grid String Inverter

SPI3K~6K-B2



Product Features

High efficiency

- High-efficiency inverter topology ensures annual power generation
- Advanced control algorithms and high adaptation ability to the grid, improving the stability of power generation system

Safe and reliable

- IP65 for outdoor application
- Integrated AC/DC full lightning protection
- Aluminum alloy die-casting integrated chassis, ensure 25 years full life circle running


Intelligent management

- Intelligent cloud platform monitoring, realizing one- key APP real-time monitoring
- Support RS485, GPRS, WIFI and other communication methods

Green saving

- Small size, easy to install and use
- Natural cooling, ensuring low environmental noise
- Super-wide operating temperature range, adapt to extremely cold, high temperature areas

Function Diagram



Technical Specification

Items	SPI3000-B2	SPI3600-B2	SPI4000-B2	SPI4600-B2	SPI5000-B2	SPI6000-B2
DC Input						
Max. PV input voltage	600Vdc					
Rated input voltage	360Vdc					
Max. PV input current	26A					
No. of MPPTs	2					
No.of PV strings per MPPT	1/1					
MPPT voltage range	100Vdc~550Vdc					
Starting voltage	120Vdc					
AC Output						
Rated AC output power	3.0kW	3.6kW	4.0kW	4.6kW	5.0kW	6.0kW
Max. output power	3.3kVA	3.96kVA	4.4kVA	5.06kVA	5.5kVA	6.0kVA
Rated AC output voltage	220V/230Vac					
Rated output current	13.0A	15.7A	17.4A	20.0A	21.7A	26.0A
Max. output current	14.3A	17.2 A	19.1A	22.0 A	23.9 A	26.0 A
Rated grid frequency	50/60Hz					
Grid frequency range	45~55Hz/55~65Hz					
Power factor	>0.99 (rated power)					
Adjustable power factor	0.8(leading)~0.8(lagging)					
THDI	<3% (rated power)					
Efficiency						
Max. efficiency	98.10%					98.30%
European efficiency	97.70%					97.90%
Protection						
Anti-islanding	Yes					
DC reversed connection	Yes					
AC short circuit protection	Yes					
Temperature protection	Yes					
Surge protection	Yes					
PV fault detect	Yes					
DC switch	Yes (optional)					
General						
Dimensions (W×H×D)	360×420×125mm					
Weight	11.5kg					
IP grade	IP65					
Noise level	≤25 dB					
Self-consumption at night	<1W					
Cooling type	Natural cooling					
Altitude	4000m (>2000m derating)					
Operating temperature	-40°C~60°C					
Operating humidity	0~100%					
Display	LCD+LED					
Communication	RS485/WIFI (optional)/GPRS (optional)/DRM (Australia)					
DC terminal	MC4/H4 Terminal					
AC terminal	Plug and play connector					
Installation method	Wall-mounted					
Standard	EN62109-1, EN62109-2, AS/NZS4777.2, EN 61000-6-2, EN 61000-6-3, IEC 62116, IEC 61727, IEC 60068-2-1, IEC 60068-2-2, IEC60068-2-14, IEC60068-2-30, VDE V0126-1-1, UTE C15-712-1, CEI 0-21					

- Specifications are subject to change without prior notice.

Kehua Tech

Add: No. 457, Malong Road, Torch High-Tech Industrial Zone, Xiamen Fujian China

Tel: +86-592-5160516 Fax: +86-592-5162166 www.kehua.com

